



MODEL 1211 MODEL 1212

SIMPLEX DUPLEX

CAPACITY GPH MAX. (PER HEAD)

PRESSURE PSIG MAX.

MOTOR: HP VOLTS HZ

PH RPM

ENCLOSURE GP TE XP

* REQUIRED FOR REMOVAL OF BELT GUARD

SIZE	A	B	C	D	E	F	G	K	L SUCTION	M DISCHARGE	
LARGE 4" DIA. HEAD	4.75	4.75	18.12	.81	13.00	14.62	11.88	1.50	5/8 OD x 5/16 ID R-15 PLASTIC TUBING	5/8 OD x 5/16 ID R-15 PLASTIC TUBING	
	4.25	4.25		.56	13.25	14.38			5/8 OD x 1/2 ID POLYETHYLENE TUBING	5/8 OD x 1/2 ID POLYETHYLENE TUBING	5/8 OD x 1/2 ID POLYETHYLENE TUBING
	3.75	4.75	17.12						1/2 NPT (MALE)	1/2 NPT (FEMALE)	1/2 NPT (MALE)
	4.75	4.75	18.12	.81	13.00	14.62			5/8 OD x 5/16 ID NYLONBRADE TUBING	5/8 OD x 5/16 ID NYLONBRADE TUBING	5/8 OD x 5/16 ID NYLONBRADE TUBING
SMALL 3" DIA. HEAD	6.25	6.25	19.62				11.62	1.50	1/2 NPT (MALE)	1/2 NPT (FEMALE)	
	3.75	3.75	17.12						1/2 NPT (FEMALE)	1/2 NPT (FEMALE)	1/2 NPT (FEMALE)
	4.75	7.00	18.12						5/8 OD x 5/16 ID R-15 PLASTIC TUBING	5/8 OD x 5/16 ID R-15 PLASTIC TUBING	5/8 OD x 5/16 ID R-15 PLASTIC TUBING
	3.12	3.12	16.50	.56	13.25	14.38			3/8 OD x 1/4 ID POLYETHYLENE TUBING	3/8 OD x 1/4 ID POLYETHYLENE TUBING	3/8 OD x 1/4 ID POLYETHYLENE TUBING
	2.38	2.38	15.62						1/4 NPT (FEMALE)	1/4 NPT (FEMALE)	
	2.38	3.12	15.62						3/8 OD x 1/4 ID POLYETHYLENE TUBING	1/4 NPT (FEMALE)	

Ref. 1210.42-1